

# MDSC-2226

Full HD 26-inch surgical display



- For the best hand-eye coordination
- Allows for easy cleaning and disinfection
- Works with Nexxis for video-over-IP integration

Barco's MDSC-2226 is a 26-inch near-patient surgical display with LED backlight. Purpose-built for the operating room, the MDSC-2226 offers an easy-clean design, smart mechanics and the most detailed images in the procedure room today.

### Ease of mind

Calibrated, artifact-free images

The display's high brightness, high contrast and full HD resolution provide surgeons with excellent depth perception and the most accurate images. The MDSC-2226 presents images with unrivaled color and grayscale accuracy and with near-zero latency, making it perfectly suited for use with today's state-of-the-art endoscopy camera systems. Thanks to its high-bright LED backlight with light output stabilization, the surgical display also ensures a long lifetime and image consistency across displays.

Multi-source, multi-display imaging

With its broad input connectivity, the MDSC-2226 offers flexible multi-modality imaging (PiP & PaP) in new integrated operating rooms. The 26-inch display is also the first surgical display offering integrated functionality (optional) for use with Barco's Nexxis for OR solution, ensuring smooth distribution of uncompressed video and data over the IP network without delay.

### Ease of installation

The MDSC-2226 comes with a smart cable management system that hides the cables for a clutter-free set-up. Its lightweight design allows easy mounting on surgical booms and spring arms. Available in three models, this surgical display also features a host of connectivity options and remote control.

**Ease of use**

Barco's MDSC-2226 allows easy cleaning and disinfection thanks to its smooth surface, splash-proof housing (front protection level IPX5), and protective screen cover. The fanless design avoids the spread of contaminants.

Barco's MDSC-2226 features:

- 26" wide-screen LCD
- Full HD resolution (1,920 x 1,080)
- High-bright LED backlight with output stabilization
- Wide viewing angle thanks to IPS-Pro LCD technology
- 10-bit image processing
- 12-bit look-up table
- Artifact-free images
- Calibrated, consistent colors and grayscales
- Easy-clean design with sealed front (IPX5)
- Smart cable management system

**Product specifications****MDSC-2226**

<b>General specifications</b>	
Screen technology	TFT AM LCD (LED backlight)
Active screen size (diagonal)	661 mm (26")
Active screen size (H x V)	576 x 324 mm (22.7" x 12.8")
Aspect ratio	16:9
Resolution	2MP (1920 x 1080)
Pixel pitch	0.3 mm
Color imaging	Yes
Color support	> 1 billion
Color gamut	100% ITU-R BT.709 HD standard
Viewing angle	178°
Maximum luminance	450 cd/m <sup>2</sup> (typ.)
Contrast ratio	1400:1
Housing color	White
Video inputs	DVI-I Single link (with HDMI support) RGBS / YPbPr (4xBNC) S-video (4-pin Mini DIN) Composite video (1xBNC) 3G-SDI (1xBNC) VGA (on DVI-I) DisplayPort (VESA std 1.1a)  Options: DDI (Dual Digital Input): additional DVI-D and 3G-SDI input Nexxis MNA-120 decoder (for uncompressed video-over-IP)
Video outputs	DVI-D x1 S-video (4-pin Mini DIN) Composite video (1xBNC) 3G-SDI (1xBNC)  Option: DDI (Dual Digital Input) : additional 3G-SDI output
Remote control	RS-232 (D-sub p-pin)
Power requirements (nominal)	100-250 V / 47-63 Hz auto-switch 120W max
Power management	DVI-DMPM states supported Power On state Active-Off state
OSD languages	English, French, German, Spanish, Italian
Dimensions w/o stand (W x H x D)	633 x 411 x 90 mm (24.9 x 16.2 x 3.5")
Net weight w/o stand	9.4 kg / 20.7 lbs (MDSC-2226 LED) 9.8 kg / 21.6 lbs (MDSC-2226 MNA)
Net weight packaged w/o stand	12.5 kg (27.6 lbs)
Mounting standard	VESA (100 mm)
Screen protection	Protective, non-reflective PMMA cover
Recommended modalities	Endoscopy, US, X-ray
Regulation Compliance	IEC60601 3rd Edition Approvals/Marking: CE, C-UL-US, DEMKO Safety (Medical equipment): IEC60601-1, UL60601-1, CAN/CSA C22.2 No. 60601-1-08 Electromagnetic compatibility: EMC Medical EMC standards: IEC60601-1-2, EN55011 / CISPR 11, FCC CFR47 part 15 & 18/Class B Protection level: IP21 (with Protection screen) / Front face: IPX5 protection level Green requirements: ROHS2, REACH, WEEE compliant
Supplied accessories	User Manual Mains cables: EU (CEBEC/KEMA) & US (Hospital grade UL) External power supply
Optional accessories	Barco MDSC surgical medical LCD display desk stand
Warranty	3 years

Last updated: 16 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.